HONDA > CRF AFRICA TWIN > MG456-395HRW







Specification

UPGRADE YOUR HONDA CRF 1000L AFRICA TWIN WITH 3 ADJUSTABLE FUNCTIONS

- > HYDRAULIC SPRING PRELOAD Adjust the Preload of the Spring relative to the Weight of The Rider using hydraulic cylinder.
- > REBOUND ADJUSTABLE Adjust the Rebound to Control the Spring outgoing Shock Movement. Fast or slow depending on your needs
- > HI-LOW SPEED ADJUSTABLE Adjustable Hi-Low Speed Compression a zenith of the compression control technology. HI-LOW valve is designed to maintain and control the flow and the high speed valve is set to active when the oil pressure is too high so the shocks will not get Hydraulic Lock.

RELATED PRODUCTS



MZ465-420TRL

Rear Mono Shock

YSS GAS SHOCK ABSORBER FOR HONDA CRF 250 RALLY (2016 - 2017). BOOST THE PERFORMANCE AND FEELING WHEN RIDING WITH 3 ADJUSTABLE FUNCTION

- ▶ Can adjust the spring preload by tread spring preload.
- ▶ Can Adjust the Rebound to Control the Spring outgoing Shock Movement. Fast or slow depending on your needs
- Can adjust the length of Shock Absorber longer 5 mm.







